

VTCP UO KUQT'UQP QTQ

Modelc : TR-SLT1A4

ISO-9001, CE, IEC1010



7cbffc`UXcf`4-20 mA /AlarmY/IndicaXor

Modelc : CT-2002-MA

Lutron

LUTRON ELECTRONIC

impac

www.impact.com.br

SOUND LEVEL TRANSMITTER

Model : TR-SLT1A4

| | |
|------------------------------|---|
| Measure Range | <p><i>Range 1 :</i> 30 - 80 dB</p> <p><i>Range 2 :</i> 50 - 100 dB</p> <p><i>Range 3 :</i> 80 - 130 dB</p> |
| Output | <p>4 - 20 mA</p> <p><i>Range 1 :</i> 30 dB:7.69 mA 80 dB:13.84mA</p> <p><i>Range 2 :</i> 50dB:10.15 mA 100dB:16.3mA</p> <p><i>Range 3 :</i> 80dB:13.84mA 130 dB:20 mA</p> |
| External Adjustment | 94 dB Cal. VR |
| Power Supply | 90 - 260 ACV 50 Hz/60 Hz |
| Operation Temperature | 0 - 50 °C 32 - 122 °F |
| Operation Humidity | Less than 80 %RH |
| Accessory Included | Sound level Probe |
| Optional Accessories | Sound calibrator SC-941 (94 dB) SC-942 (94 dB/114 dB) |
| Mounting Case | Din rail or Wall ABS plastic |
| Others | Separate probe |

* Appearance and specifications listed in this brochure are subject to change without notice.